

OW20 Fully synthetic

PRODUCT DATA SHEET

DESCRIPTION

FUELUBE 0W-20 engine oil with **ESTER** and **PAO** is a premium synthetic oil designed for high efficiency and protection. The 0W-20 viscosity ensures excellent cold-start performance and fuel economy, while providing sufficient protection in hot conditions. Ester base oils offer strong polar properties, adhering to metal surfaces for enhanced lubrication, reducing wear and tear. PAO (Polyalphaolefin) provides superior thermal stability, oxidation resistance, and excellent low-temperature fluidity.

APPLICATION

This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It has a low viscosity formulation that meets the more demanded OEM specifications.

FEATURES AND ADVANTAGES

- PERFORMANCE
- PROTECTION
- ENGINE CLEANINESS

PRODUCT PERFORMANCE CLAIM

- API SP/ SN/ SN PLUS/ SM/ SL/ SJ/ ILSAC GF-6A
- ACEA A3/B4-21, ACEA C3-21
- BMW Longlife 04
- MB-Approval 229.71, 229.5
- Porsche A40
- VW502 00/505 00
- RENAULT RN0700/RN0710
- CHRYSLER MS-6395G
- HONDA/ACURA HTO-06
- FORD WSS-M2C962-A1, M2C946-B1
- GENERAL MOTORS GM 4718 M, 6094 M
- FIAT 9.55535-CR
- Jaguar / Land Rover STJLR.03.5006







PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @15°C	ASTM D4052	kg/m³	854.9
Kinematic Viscosity @40°C	ASTM D7042	mm²/s	73.842
Kinematic Viscosity @100°C	ASTM D7042	mm²/s	7.601
Viscosity index	ASTM D2270	-	170.99
Pour point	ASTM D97	°C	-40
Flash point	IP 523	°C	220

^{*}VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

