



0W30 Fully synthetic

PRODUCT DATA SHEET

DESCRIPTION

FUELUBE 0W-30 engine oil formulated with **ESTER** and **PAO (Polyalphaolefin)** provides superior performance for high-performance and modern engines. The ester component enhances lubrication by offering excellent film strength, ensuring protection even in extreme temperatures. PAO, a synthetic base oil, delivers outstanding thermal stability and low volatility, reducing oil consumption.

APPLICATION

This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It has a low viscosity formulation that meets the more demanded OEM specifications.

FEATURES AND ADVANTAGES

- PERFORMANCE
- PROTECTION
- ENGINE CLEANINESS

PRODUCT PERFORMANCE CLAIM

- API SP/ SN/ SN PLUS/ SM/ SL/ SJ/ ILSAC GF-6A
- ACEA A3/B4-21, ACEA C3-21
- Ford WSS-M2C947-A
- FIAT 9.55535-GS1
- BMW Longlife-12 FE
- MB-APPROVAL 227.61/229.61
- GM 6094 M
- GM-LL-A-025
- Chrysler MS-6395
- VOLVO 95200377
- Renault RN 0700 / RN 0710
- VW 502 00 / 505 00
- Porsche A40



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @15°C	ASTM D4052	kg/m ³	856.3
Kinematic Viscosity @40°C	ASTM D7042	mm ² /s	89.525
Kinematic Viscosity @100°C	ASTM D7042	mm ² /s	10.249
Viscosity index	ASTM D2270	-	165.17
Pour point	ASTM D97	°C	-40
Flash point	IP 523	°C	220

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

