

## PRODUCT DATA SHEET

# **10W40 CI4 SEMI SYNTHETIC**

#### **DESCRIPTION**

A premium semi-synthetic engine oil formulated with high-quality base oils and advanced additive technology. It provides reliable protection against wear, oxidation, and deposits while ensuring smooth operation under both high and low temperature conditions. With a high viscosity index and excellent thermal stability, it delivers consistent lubrication, reduced oil consumption, and extended engine life in demanding operating environments.

#### **APPLICATION**

This oil is suitable for both diesel and gasoline engines, including turbocharged and naturally aspirated units. It is recommended for passenger cars, light commercial vehicles, construction machinery, and agricultural equipment. Ideal for mixed fleet operators where a single lubricant solution is required for versatile and reliable performance.

#### **FEATURES AND ADVANTAGES**

- > Provides a strong lubricating film for engine protection
- ➤ High viscosity index ensures stable performance across wide temperature ranges
- Minimizes friction, reduces wear, and improves fuel efficiency
- Excellent detergency and dispersancy keep engines clean and deposit-free

#### PRODUCT PERFORMANCE CLAIM

API SP/CI-4 ACEA A3/B4

Volvo VDS-3, Cummins CES 20078, Renault VI RLD-2

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscocity Grade	SAE J300	-	10W40
Colour	VISUAL	-	Gold brown
Density @ 15°C	ASTM D4052	kg/m3	874.6
Kinematic Viscosity @ 40°C	ASTM D7042	mm²/s	135.13
Kinematic Viscosity @ 100°C	ASTM D7042	mm²/s	15.031
Viscosity Index	ASTM D2270	-	144.8
Pour Point, °C	ASTM D97	°C	-20
Flash Point, °C	IP 523	°C	240

<sup>\*</sup>VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

### **HEALTHY AND SAFETY**

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

