



PRODUCT DATA SHEET

ATF DEXRON-III

DESCRIPTION

A premium quality automatic transmission fluid formulated with highly refined base oils and advanced additive technology. Designed to deliver smooth shifting, excellent protection, and reliable performance in a wide range of automatic transmissions. It provides outstanding thermal stability, wear protection, and resistance to oxidation, ensuring long service life and consistent performance under severe operating conditions.

APPLICATION

Recommended for use in automatic transmissions, power steering systems, and certain hydraulic systems requiring DEXRON® III specification. Suitable for passenger cars, light trucks, buses, and off-highway equipment. Always follow OEM recommendations.

FEATURES AND ADVANTAGES

- Exceptional load-carrying and anti-wear protection under extreme pressure conditions
- Excellent thermal and oxidation stability for extended drain intervals
- Excellent protection against rust, corrosion, and foaming
- Wide operating temperature range ensures reliable performance in both cold and hot climates

PRODUCT PERFORMANCE CLAIM

Toyota : D-III, GM Dexron III F / Dexron III G , GM Type A Suffix A, Allison TES-389, Allison C-4, Mercedes Benz MB 236.1/ 236.9, Man 339 Type V1 / V2, 339 Type Z1/ Z2, Ford Mercon IV, Ford M2C-138CJ, Voith H55.6335xx, Volvo STD 1273.41(97341) Subaru ATF/ ATF HP , Mazda M III Fluid

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Viscosity Grade	SAE J300	-	DEXRON-III
Colour	VISUAL	-	RED
Density @ 15°C	ASTM D4052	kg/m ³	857.2
Kinematic Viscosity @ 40°C	ASTM D7042	mm ² /s	37.076
Kinematic Viscosity @ 100°C	ASTM D7042	mm ² /s	7.5798
Viscosity Index	ASTM D2270	-	178.51
Pour Point, °C	ASTM D97	°C	-31
Flash Point, °C	IP 523	°C	210

****VALUES SHOWN HERE ARE TYPICAL AND MAY VARY***

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

