



ATF TYPE IV

PRODUCT DATA SHEET

DESCRIPTION

FUELUBE ATF Type IV is a high-performance automatic transmission fluid formulated for vehicles requiring Toyota Type T-IV specifications. It provides smooth shifting, reliable friction control, excellent wear protection, and resistance to heat and oxidation. Its advanced formulation helps maintain clean transmission components and dependable performance in a wide range of driving conditions. Always check the vehicle manufacturer's service manual before use.

PRODUCT PERFORMANCE CLAIM

- Aisin Warner JWS 3309
- Toyota / Lexus Type T-II / T-III / T-IV
- GM DEXRON® II / III
- Ford MERCON V
- Honda ATF Z1 (except CVTs)
- Hyundai / Kia SP-II / SP-III
- Mitsubishi SP-II / SP-III
- Mazda ATF M-III / M-V
- Nissan Matic-D / J / K
- Subaru ATF / ATF-HP
- Daihatsu Ammix ATF D-II / D-III SP



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @15°C	ASTM D4052	kg/m ³	856.7
Kinematic Viscosity @40°C	ASTM D7042	mm ² /s	35.71
Kinematic Viscosity @100°C	ASTM D7042	mm ² /s	7.5443
Viscosity index	ASTM D2270	-	176.97
Pour point	ASTM D97	°C	-45
Flash point	IP 523	°C	210

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.



All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which our company and its affiliates assume legal responsibility.