



ATF WS

PRODUCT DATA SHEET

DESCRIPTION

FUELUBE ATF WS is a premium low-viscosity automatic transmission fluid formulated for vehicles requiring WS-type fluid. It delivers smooth and responsive shifting, excellent low-temperature flow, strong wear protection and oxidation stability. Its advanced friction-control properties help reduce shudder, protect critical transmission components and maintain reliable performance under demanding driving conditions.

PRODUCT PERFORMANCE CLAIM

- TOYOTA WS, TYPE T-IV
- Honda DW-1
- Mitsubishi DiaQueen J3
- Mazda ATF FZ
- Nissan Matic D / J / K / S
- Hyundai / Kia SP-IV, SP-IV M
- Jaguar ATF 3403 / LT71141
- ZF 5HP24 / ZF 6 Speed
- Suzuki ATF 3314 / 3317
- AISIN WARNER AW-1
- Lexus ATF WS



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @15°C	ASTM D4052	kg/m ³	858.5
Kinematic Viscosity @40°C	ASTM D7042	mm ² /s	51.931
Kinematic Viscosity @100°C	ASTM D7042	mm ² /s	9.7999
Viscosity index	ASTM D2270	-	177.67
Pour point	ASTM D97	°C	-42
Flash point	IP 523	°C	210

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.



All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which our company and its affiliates assume legal responsibility.