



PRODUCT DATA SHEET

ANTI-FREEZE COOLANT 50/50

DESCRIPTION

ANTI-FREEZE COOLANT 50/50 is a ready-to-use, pre-mixed coolant designed to provide excellent protection against overheating, rust, and corrosion. Its 50/50 blend of high-quality antifreeze and deionized water ensures optimal engine cooling performance in all climates, preventing freezing in cold conditions and boil-over in high temperatures. It extends radiator and water pump life by maintaining a stable operating temperature and preventing scale build-up. No dilution required—just pour and protect your engine with long-lasting reliability.

APPLICATION

Suitable for all gasoline and diesel engines. Provides year-round protection against rust, corrosion, freezing, and overheating. Ready-to-use 50/50 mix—no dilution required. Ideal for radiators, water pumps, and complete cooling systems in cars, trucks, and heavy-duty vehicles.

FEATURES AND ADVANTAGES

- Prevents rust & corrosion
- Protects in all climates
- Extends engine component life
- Ready-to-use convenience

PRODUCT PERFORMANCE CLAIM

ASTM D-3306, ASTM D-4985, GM 6277M, SAE J1034, SAE J814, SAE J1941, EMD MI 1748, TMC RP-302C, NB/SH/T 0521-2010, A-A-870A

PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @ 15°C	ASTM D4052	kg/m3	1070
Colour	VISUAL	-	RED, GREEN, BLUE, PINK
pH	ASTM D1287	mm2 /s	8.0
Freezing point	ASTM D1177	°C	-30
Boiling point	ASTM D1120	°C	110

****VALUES SHOWN HERE ARE TYPICAL AND MAY VARY***

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.

