



POWER STEERING FLUID

PRODUCT DATA SHEET

DESCRIPTION

FUELUBE POWER STEERING FLUID is a premium hydraulic fluid formulated to help maintain smooth, responsive and reliable power steering performance. Its advanced anti-wear and oxidation-resistant properties help protect steering pumps, seals and system components from wear, corrosion and deposit formation. It also helps reduce steering noise and delivers stable performance across a wide temperature range.

PRODUCT PERFORMANCE CLAIM

- HONDA P/N 08206-9002A, PSF-2, PSF TYPE S, PSF TYPE V
- AMC 4124
- BOSCH TE-ML 09
- CHRYSLER MS-1872, MS-5931
- FORD ESW-M2C128-C, ESW-M2C128-D, M2C195-A
- GM 9985010, P/N 1052884, P/N 89021184
- HYUNDAI / KIA PSF-3
- MB 236.3
- MITSUBISHI PS FLUID
- NISSAN PSF-II
- SAAB P/N (45)30 09 800
- SUBARU P/N K0209A0080
- ZF TE-ML 05L, TE-ML 21L



PARAMETER	METHOD	UNIT	TYPICAL RESULT
Density @15°C	ASTM D4052	kg/m ³	855.7
Kinematic Viscosity @40°C	ASTM D7042	mm ² /s	31.106
Kinematic Viscosity @100°C	ASTM D7042	mm ² /s	6.0895
Viscosity index	ASTM D2270	-	147.14
Pour point	ASTM D97	°C	-45
Flash point	IP 523	°C	210

***VALUES SHOWN HERE ARE TYPICAL AND MAY VARY**

HEALTHY AND SAFETY

Based on available information, no adverse health effects are expected when this product is used for its intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS requests are available through your sales contract office or via the Internet. This product should not be used for purposes other than its intended use. If handling used products, take care to protect the environment.



All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which our company and its affiliates assume legal responsibility.